

360LAMP

Downlights Collection





ALITA ADJUSTABLE NXAL-072-05-AD

Vendor: 360LAMP

Light Source: 5.3W-520lm-2700K , 5.3W-520lm-3000K , 5.3W-520lm-4000K ,

Driver: O-On/Off , DIM1-1~10V , DIM2-DALI ,

Accessories: None , Honeycomb , Softening Lens ,

BUY NOW

Description

Adjustable compact LED downlight with round white frame. Recessed downlight for cut-out ceiling openings. Tool-free ceiling installation via rapid-mounting springs. Cut-out opening Ø 65 mm, Recess depth 80 mm. Aluminium reflector highly specular anodized. Glare evaluation according to UGR < 19. Configured with one LED adjustable spot module. Light colour warm white, correlated colour temperature (CCT) 2700 K, 3000K and 4000K. General colour rendering index (CRI) $R_a > 90$. Mean rated service life $L_{70}(t_q\ 25\ ^\circ\text{C}) = 50,000\ \text{h}$. Luminaire body of die-cast aluminium. Surface coated dark grey. Luminaire body and heat sink form a compact unit. Protection rating: IP20. With an electronic transformer, switchable.

Specification

Model No.	NXAL-072-05-AD
Light Source	5.3W-520lm-2700K/ 3000K/ 4000K
CRI	90
Driver	O-OnOff/ DIM1-1~10V/ DIM2-DALI
Reflector color	Black/ White
Light beam angle	15°/ 24°/ 38°/ 48°
Accessories	Honeycomb/ Softening Lens
Dimension	Ø72 mm*H80 mm
Cut-out	Ø65 mm



ALITA ADJUSTABLE NXAL-072-08-AD

Vendor: 360LAMP

Light Source: 8.3W-788lm-2700K , 8.3W-788lm-3000K , 8.3W-788lm-4000K ,

Driver: O-On/Off , DIM1-1~10V , DIM2-DALI ,

Accessories: None , Honeycomb , Softening Lens ,

BUY NOW

Description

Adjustable compact LED downlight with round white frame. Recessed downlight for cut-out ceiling openings. Tool-free ceiling installation via rapid-mounting springs. Cut-out opening Ø 65 mm, Recess depth 80 mm. Aluminium reflector highly specular anodized. Glare evaluation according to UGR < 19. Configured with one LED adjustable spot module. Light colour warm white, correlated colour temperature (CCT) 2700 K, 3000K and 4000K. General colour rendering index (CRI) $R_a > 90$. Mean rated service life $L_{70}(t_q\ 25\ ^\circ\text{C}) = 50,000\ \text{h}$. Luminaire body of die-cast aluminium. Surface coated dark grey. Luminaire body and heat sink form a compact unit. Protection rating: IP20. With an electronic transformer, switchable.

Specification

Model No.	NXAL-072-08-AD
Light Source	8.3W-788lm-2700K/ 3000K/ 4000K
CRI	90
Driver	O-OnOff/ DIM1-1~10V/ DIM2-DALI
Reflector color	Black/ White
Light beam angle	15°/ 24°/ 38°/ 48°
Accessories	Honeycomb/ Softening Lens
Dimension	Ø72 mm*H80 mm
Cut-out	Ø65 mm



ALITA ADJUSTABLE NXAL-082-08-AD

Vendor: 360LAMP

Light Source: 8.3W-788lm-2700K , 8.3W-788lm-3000K , 8.3W-788lm-4000K ,

Driver: O-On/Off , DIM1-1~10V , DIM2-DALI ,

Accessories: None , Honeycomb , Softening Lens ,

BUY NOW

Description

Adjustable compact LED downlight with round construction. Recessed downlight for cut-out ceiling openings. Tool-free ceiling installation via rapid-mounting springs. Cut-out opening Ø 75 mm, Recess depth 85 mm. Aluminium reflector highly specular anodized. Glare evaluation according to UGR < 19. Configured with one LED adjustable spot module. Light colour warm white, correlated colour temperature (CCT) 2700 K, 3000K and 4000K. General colour rendering index (CRI) $R_a > 90$. Mean rated service life $L_{70}(t_q\ 25\ ^\circ\text{C}) = 50,000\ \text{h}$. Luminaire body of die-cast aluminium. Surface coated dark grey. Luminaire body and heat sink form a compact unit. Protection rating: IP20. With an electronic transformer, switchable.

Specification

Model No.	NXAL-082-08-AD
Light Source	8.3W-788lm-2700K/ 3000K/ 4000K
CRI	90
Driver	O-OnOff/ DIM1-1~10V/ DIM2-DALI
Reflector color	Black/ White
Light beam angle	15°/ 24°/ 38°/ 48°
Accessories	Honeycomb/ Softening Lens
Dimension	Ø82 mm*H85 mm
Cut-out	Ø75 mm



ALITA ADJUSTABLE NXAL-082-10-AD

Vendor: 360LAMP

Light Source: 10.5W-1050lm-2700K , 10.5W-1050lm-3000K , 10.5W-1050lm-4000K ,

Driver: O-On/Off , DIM1-1~10V , DIM2-DALI ,

Accessories: None , Honeycomb , Softening Lens ,

BUY NOW

Description

Adjustable compact LED downlight with round construction. Recessed downlight for cut-out ceiling openings. Tool-free ceiling installation via rapid-mounting springs. Cut-out opening Ø 75 mm, Recess depth 85 mm. Aluminium reflector highly specular anodized. Glare evaluation according to UGR < 19. Configured with one LED adjustable spot module. Light colour warm white, correlated colour temperature (CCT) 2700 K, 3000K and 4000K. General colour rendering index (CRI) $R_a > 90$. Mean rated service life $L_{70}(t_q 25\text{ }^{\circ}\text{C}) = 50,000\text{ h}$. Luminaire body of die-cast aluminium. Surface coated dark grey. Luminaire body and heat sink form a compact unit. Protection rating: IP20. With an electronic transformer, switchable.

Specification

Model No.	NXAL-082-10-AD
Light Source	10.5W-1050lm-2700K/ 3000K/ 4000K
CRI	90
Driver	O-OnOff/ DIM1-1~10V/ DIM2-DALI
Reflector color	Black/ White
Light beam angle	15°/ 24°/ 38°/ 48°
Accessories	Honeycomb/ Softening Lens
Dimension	Ø82 mm*H85 mm
Cut-out	Ø75 mm



ALITA ADJUSTABLE NXAL-082-12-AD

Vendor: 360LAMP

Light Source: 12.5W-1092lm-2700K , 12.5W-1092lm-3000K , 12.5W-1092lm-4000K ,

Driver: O-On/Off , DIM1-1~10V , DIM2-DALI ,

Accessories: None , Honeycomb , Softening Lens ,

BUY NOW

Description

Adjustable compact LED downlight with round construction. Recessed downlight for cut-out ceiling openings. Tool-free ceiling installation via rapid-mounting springs. Cut-out opening Ø 75 mm, Recess depth 85 mm. Aluminium reflector highly specular anodized. Glare evaluation according to UGR < 19. Configured with one LED adjustable spot module. Light colour warm white, correlated colour temperature (CCT) 2700 K, 3000K and 4000K. General colour rendering index (CRI) R_a > 90. Mean rated service life L₇₀(t_q 25 °C) = 50,000 h. Luminaire body of die-cast aluminium. Surface coated dark grey. Luminaire body and heat sink form a compact unit. Protection rating: IP20. With an electronic transformer, switchable.

Specification

Model No.	NXAL-082-12-AD
Light Source	12.5W-1092lm-2700K/ 3000K/ 4000K
CRI	90
Driver	O-OnOff/ DIM1-1~10V/ DIM2-DALI
Reflector color	Black/ White
Light beam angle	15°/ 24°/ 38°/ 48°
Accessories	Honeycomb/ Softening Lens
Dimension	Ø82 mm*H85 mm
Cut-out	Ø75 mm



ALITA ADJUSTABLE NXAL-115-15-AD

Vendor: 360LAMP

Light Source: 15W-1650lm-2700K , 15W-1650lm-3000K , 15W-1650lm-4000K ,

Driver: O-On/Off , DIM1-1~10V , DIM2-DALI ,

Accessories: None , Honeycomb , Softening Lens ,

BUY NOW

Description

Adjustable compact LED downlight with round white frame. Recessed downlight for cut-out ceiling openings. Tool-free ceiling installation via rapid-mounting springs. Cut-out opening Ø 100 mm, Recess depth 120 mm. Aluminium reflector highly specular anodized. Glare evaluation according to UGR < 19. Configured with one LED adjustable spot module. Light colour warm white, correlated colour temperature (CCT) 2700 K, 3000K and 4000K. General colour rendering index (CRI) $R_a > 90$. Mean rated service life $L_{70}(t_q 25\text{ }^{\circ}\text{C}) = 50,000\text{ h}$. Luminaire body of die-cast aluminium. Surface coated dark grey. Luminaire body and heat sink form a compact unit. Protection rating: IP20. With an electronic transformer, switchable.

Specification

Model No.	NXAL-115-15-AD
Light Source	15W-1650lm-2700K/ 3000K/ 4000K
CRI	90
Driver	O-OnOff/ DIM1-1~10V/ DIM2-DALI
Reflector color	Black/ White
Light beam angle	15°/ 24°/ 38°/ 48°
Accessories	Honeycomb/ Softening Lens
Dimension	Ø115 mm*H120 mm
Cut-out	Ø100 mm



ALITA ADJUSTABLE NXAL-115-24-AD

Vendor: 360LAMP

Light Source: 24W-2640lm-2700K , 24W-2640lm-3000K , 24W-2640lm-4000K ,

Driver: O-On/Off , DIM1-1 $\frac{1}{2}$ 10V , DIM2-DALI ,

Accessories: None , Honeycomb , Softening Lens ,

BUY NOW

Description

Adjustable compact LED downlight with round white frame. Recessed downlight for cut-out ceiling openings. Tool-free ceiling installation via rapid-mounting springs. Cut-out opening Ø 100 mm, Recess depth 120 mm. Aluminium reflector highly specular anodized. Glare evaluation according to UGR < 19. Configured with one LED adjustable spot module. Light colour warm white, correlated colour temperature (CCT) 2700 K, 3000K and 4000K. General colour rendering index (CRI) $R_a > 90$. Mean rated service life $L_{70}(t_q\ 25\ ^\circ C) = 50,000\ h$. Luminaire body of die-cast aluminium. Surface coated dark grey. Luminaire body and heat sink form a compact unit. Protection rating: IP20. With an electronic transformer, switchable.

Specification

Model No.	NXAL-115-24-AD
Light Source	24W-2640lm-2700K/ 3000K/ 4000K
CRI	90
Driver	O-OnOff/ DIM1-1 $\frac{1}{2}$ 10V/ DIM2-DALI
Reflector color	Black/ White
Light beam angle	15°/ 24°/ 38°/ 48°
Accessories	Honeycomb/ Softening Lens
Dimension	Ø115 mm*H120 mm
Cut-out	Ø100 mm



ALITA ADJUSTABLE NXAL-140-15-AD

Vendor: 360LAMP

Light Source: 15W-1650lm-2700K , 15W-1650lm-3000K , 15W-1650lm-4000K ,

Driver: O-On/Off , DIM1-1~10V , DIM2-DALI ,

Accessories: None , Honeycomb , Softening Lens ,

BUY NOW

Description

Adjustable compact LED downlight with round white frame. Recessed downlight for cut-out ceiling openings. Tool-free ceiling installation via rapid-mounting springs. Cut-out opening Ø 125 mm, Recess depth 130 mm. Aluminium reflector highly specular anodized. Glare evaluation according to UGR < 19. Configured with one LED adjustable spot module. Light colour warm white, correlated colour temperature (CCT) 2700 K, 3000K and 4000K. General colour rendering index (CRI) $R_a > 90$. Mean rated service life $L_{70}(t_q\ 25\ ^\circ C) = 50,000\ h$. Luminaire body of die-cast aluminium. Surface coated dark grey. Luminaire body and heat sink form a compact unit. Protection rating: IP20. With an electronic transformer, switchable.

Specification

Model No.	NXAL-140-15-AD
Light Source	15W-1650lm-2700K/ 3000K/ 4000K
CRI	90
Driver	O-OnOff/ DIM1-1~10V/ DIM2-DALI
Reflector color	Black/ White
Light beam angle	15°/ 24°/ 38°/ 48°
Accessories	Honeycomb/ Softening Lens
Dimension	Ø140 mm*H130 mm
Cut-out	Ø125 mm



ALITA ADJUSTABLE NXAL-140-24-AD

Vendor: 360LAMP

Light Source: 24W-2640lm-2700K , 24W-2640lm-3000K , 24W-2640lm-4000K ,

Driver: O-On/Off , DIM1-1~10V , DIM2-DALI ,

Accessories: None , Honeycomb , Softening Lens ,

BUY NOW

Description

Adjustable compact LED downlight with round white frame. Recessed downlight for cut-out ceiling openings. Tool-free ceiling installation via rapid-mounting springs. Cut-out opening Ø 125 mm, Recess depth 130 mm. Aluminium reflector highly specular anodized. Glare evaluation according to UGR < 19. Configured with one LED adjustable spot module. Light colour warm white, correlated colour temperature (CCT) 2700 K, 3000K and 4000K. General colour rendering index (CRI) $R_a > 90$. Mean rated service life $L_{70}(t_q 25\text{ }^{\circ}\text{C}) = 50,000\text{ h}$. Luminaire body of die-cast aluminium. Surface coated dark grey. Luminaire body and heat sink form a compact unit. Protection rating: IP20. With an electronic transformer, switchable.

Specification

Model No.	NXAL-140-24-AD
Light Source	24W-2640lm-2700K/ 3000K/ 4000K
CRI	90
Driver	O-OnOff/ DIM1-1~10V/ DIM2-DALI
Reflector color	Black/ White
Light beam angle	15°/ 24°/ 38°/ 48°
Accessories	Honeycomb/ Softening Lens
Dimension	Ø140 mm*H130 mm
Cut-out	Ø125 mm



ALITA NXAL-040-03

Vendor: 360LAMP

Light Source: 3W-330lm-2700K , 3W-330lm-3000K , 3W-330lm-4000K ,

Driver: O-On/Off , DIM1-1~10V , DIM2-DALI ,

Accessories: None , Honeycomb , Softening Lens ,

BUY NOW

Description

Compact LED downlight with round white frame. Recessed downlight for cut-out ceiling openings. Tool-free ceiling installation via rapid-mounting springs. Cut-out opening Ø35 mm, Recess depth 80 mm. Aluminium reflector highly specular anodized. Glare evaluation according to UGR < 19. Configured with one LED spot module. Light colour warm white, correlated colour temperature (CCT) 2700 K, 3000K and 4000K. General colour rendering index (CRI) R_a > 90. Mean rated service life L₇₀(t_q 25 °C) = 50,000 h. Luminaire body of die-cast aluminium. Surface coated dark grey. Luminaire body and heat sink form a compact unit. Protection rating: IP20. With an electronic transformer, switchable.

Specification

Model No.	NXAL-040-03
Light Source	3W-330lm-2700K/ 3000K/ 4000K
CRI	90
Driver	O-OnOff/ DIM1-1~10V/ DIM2-DALI
Reflector color	Black
Light beam angle	12°/ 24°/ 38°
Accessories	Honeycomb/ Softening Lens
Dimension	Ø40 mm*H75 mm
Cut-out	Ø35 mm



ALITA NXAL-040-07

Vendor: 360LAMP

Light Source: 7W-770lm-2700K , 7W-770lm-3000K , 7W-770lm-4000K ,

Driver: O-On/Off , DIM1-1~10V , DIM2-DALI ,

Accessories: None , Honeycomb , Softening Lens ,

BUY NOW

Description

Compact LED downlight with round white frame. Recessed downlight for cut-out ceiling openings. Tool-free ceiling installation via rapid-mounting springs. Cut-out opening Ø35mm, Recess depth 80 mm. Aluminium reflector highly specular anodized. Glare evaluation according to UGR < 19. Configured with one LED spot module. Light colour warm white, correlated colour temperature (CCT) 2700 K, 3000K and 4000K. General colour rendering index (CRI) R_a > 90. Mean rated service life L₇₀(t_q 25 °C) = 50,000 h. Luminaire body of die-cast aluminium. Surface coated dark grey. Luminaire body and heat sink form a compact unit. Protection rating: IP20. With an electronic transformer, switchable.

Specification

Model No.	NXAL-040-07
Light Source	7W-770lm-2700K/ 3000K/ 4000K
CRI	90
Driver	O-OnOff/ DIM1-1~10V/ DIM2-DALI
Reflector color	Black
Light beam angle	12°/ 24°/ 38°
Accessories	Honeycomb/ Softening Lens
Dimension	Ø40 mm*H75 mm
Cut-out	Ø35 mm



ALITA NXAL-050-03

Vendor: 360LAMP

Light Source: 3W-330lm-2700K , 3W-330lm-3000K , 3W-330lm-4000K ,

Driver: O-On/Off , DIM1-1~10V , DIM2-DALI ,

Accessories: None , Honeycomb , Softening Lens ,

BUY NOW

Description

Compact LED downlight with round white frame. Recessed downlight for cut-out ceiling openings. Tool-free ceiling installation via rapid-mounting springs. Cut-out opening Ø45 mm, Recess depth 80 mm. Aluminium reflector highly specular anodized. Glare evaluation according to UGR < 19. Configured with one LED spot module. Light colour warm white, correlated colour temperature (CCT) 2700 K, 3000K and 4000K. General colour rendering index (CRI) R_a > 90. Mean rated service life L₇₀(t_q 25 °C) = 50,000 h. Luminaire body of die-cast aluminium. Surface coated dark grey. Luminaire body and heat sink form a compact unit. Protection rating: IP20. With an electronic transformer, switchable.

Specification

Model No.	NXAL-050-03
Light Source	3W-330lm-2700K/ 3000K/ 4000K
CRI	90
Driver	O-OnOff/ DIM1-1~10V/ DIM2-DALI
Reflector color	Black
Light beam angle	12°/ 24°/ 38°
Accessories	Honeycomb/ Softening Lens
Dimension	Ø50 mm*H80 mm
Cut-out	Ø45 mm



ALITA NXAL-050-07

Vendor: 360LAMP

Light Source: 7W-770lm-2700K , 7W-770lm-3000K , 7W-770lm-4000K ,

Driver: O-On/Off , DIM1-1~10V , DIM2-DALI ,

Accessories: None , Honeycomb , Softening Lens ,

[BUY NOW](#)

Description

Compact LED downlight with round white frame. Recessed downlight for cut-out ceiling openings. Tool-free ceiling installation via rapid-mounting springs. Cut-out opening Ø45 mm, Recess depth 80 mm. Aluminium reflector highly specular anodized. Glare evaluation according to UGR < 19. Configured with one LED spot module. Light colour warm white, correlated colour temperature (CCT) 2700 K, 3000K and 4000K. General colour rendering index (CRI) R_a > 90. Mean rated service life L₇₀(t_q 25 °C) = 50,000 h. Luminaire body of die-cast aluminium. Surface coated dark grey. Luminaire body and heat sink form a compact unit. Protection rating: IP20. With an electronic transformer, switchable.

Specification

Model No.	NXAL-050-07
Light Source	7W-770lm-2700K/ 3000K/ 4000K
CRI	90
Driver	O-OnOff/ DIM1-1~10V/ DIM2-DALI
Reflector color	Black
Light beam angle	12°/ 24°/ 38°
Accessories	Honeycomb/ Softening Lens
Dimension	Ø50 mm*H80 mm
Cut-out	Ø45 mm



ALITA NXAL-072-05

Vendor: 360LAMP

Light Source: 5.3W-520lm-2700K , 5.3W-520lm-3000K , 5.3W-520lm-4000K ,

Driver: O-On/Off , DIM1-1~10V , DIM2-DALI ,

Accessories: None , Honeycomb , Softening Lens ,

[BUY NOW](#)

Description

Compact LED downlight with round white frame. Recessed downlight for cut-out ceiling openings. Tool-free ceiling installation via rapid-mounting springs. Cut-out opening Ø 65 mm, Recess depth 80 mm. Aluminium reflector highly specular anodized. Glare evaluation according to UGR < 19. Configured with one LED spot module. Light colour warm white, correlated colour temperature (CCT) 2700 K, 3000K and 4000K. General colour rendering index (CRI) R_a > 90. Mean rated service life L₇₀(t_q 25 °C) = 50,000 h. Luminaire body of die-cast aluminium. Surface coated dark grey. Luminaire body and heat sink form a compact unit. Protection rating: IP20. With an electronic transformer, switchable.

Specification

Model No.	NXAL-072-05
Light Source	5.3W-520lm-2700K/ 3000K/ 4000K
CRI	90
Driver	O-OnOff/ DIM1-1~10V/ DIM2-DALI
Reflector color	Black/ White
Light beam angle	15°/ 24°/ 38°/ 48°
Accessories	Honeycomb/ Softening Lens
Dimension	Ø72 mm*H80 mm
Cut-out	Ø65 mm



ALITA NXAL-072-08

Vendor: 360LAMP

Light Source: 8.3W-788lm-2700K , 8.3W-788lm-3000K , 8.3W-788lm-4000K ,

Driver: O-On/Off , DIM1-1~10V , DIM2-DALI ,

Accessories: None , Honeycomb , Softening Lens ,

BUY NOW

Description

Compact LED downlight with round white frame. Recessed downlight for cut-out ceiling openings. Tool-free ceiling installation via rapid-mounting springs. Cut-out opening Ø 65 mm, Recess depth 80 mm. Aluminium reflector highly specular anodized. Glare evaluation according to UGR < 19. Configured with one LED spot module. Light colour warm white, correlated colour temperature (CCT) 2700 K, 3000K and 4000K. General colour rendering index (CRI) R_a > 90. Mean rated service life L₇₀(t_q 25 °C) = 50,000 h. Luminaire body of die-cast aluminium. Surface coated dark grey. Luminaire body and heat sink form a compact unit. Protection rating: IP20. With an electronic transformer, switchable.

Specification

Model No.	NXAL-072-08
Light Source	8.3W-788lm-2700K/ 3000K/ 4000K
CRI	90
Driver	O-OnOff/ DIM1-1~10V/ DIM2-DALI
Reflector color	Black/ White
Light beam angle	15°/ 24°/ 38°/ 48°
Accessories	Honeycomb/ Softening Lens
Dimension	Ø72 mm*H80 mm
Cut-out	Ø65 mm



ALITA NXAL-082-08

Vendor: 360LAMP

Light Source: 8.3W-788lm-2700K , 8.3W-788lm-3000K , 8.3W-788lm-4000K ,

Driver: O-On/Off , DIM1-1 $\frac{1}{2}$ 10V , DIM2-DALI ,

Accessories: None , Honeycomb , Softening Lens ,

BUY NOW

Description

Compact LED downlight with round white frame. Recessed downlight for cut-out ceiling openings. Tool-free ceiling installation via rapid-mounting springs. Cut-out opening Ø 75 mm, Recess depth 85 mm. Aluminium reflector highly specular anodized. Glare evaluation according to UGR < 19. Configured with one LED spot module. Light colour warm white, correlated colour temperature (CCT) 2700 K, 3000K and 4000K. General colour rendering index (CRI) R_a > 90. Mean rated service life L₇₀(t_q 25 °C) = 50,000 h. Luminaire body of die-cast aluminium. Surface coated dark grey. Luminaire body and heat sink form a compact unit. Protection rating: IP20. With an electronic transformer, switchable.

Specification

Model No.	NXAL-082-08
Light Source	8.3W-788lm-2700K/ 3000K/ 4000K
CRI	90
Driver	O-OnOff/ DIM1-1 $\frac{1}{2}$ 10V/ DIM2-DALI
Reflector color	Black/ White
Light beam angle	15°/ 24°/ 38°/ 48°
Accessories	Honeycomb/ Softening Lens
Dimension	Ø82 mm*H85 mm
Cut-out	Ø75 mm



ALITA NXAL-082-10

Vendor: 360LAMP

Light Source: 10.5W-1050lm-2700K , 10.5W-1050lm-3000K , 10.5W-1050lm-4000K ,

Driver: O-On/Off , DIM1-1~10V , DIM2-DALI ,

Accessories: None , Honeycomb , Softening Lens ,

BUY NOW

Description

Compact LED downlight with round white frame. Recessed downlight for cut-out ceiling openings. Tool-free ceiling installation via rapid-mounting springs. Cut-out opening Ø 75 mm, Recess depth 85 mm. Aluminium reflector highly specular anodized. Glare evaluation according to UGR < 19. Configured with one LED spot module. Light colour warm white, correlated colour temperature (CCT) 2700 K, 3000K and 4000K. General colour rendering index (CRI) $R_a > 90$. Mean rated service life $L_{70}(t_q\ 25\ ^\circ\text{C}) = 50,000\ \text{h}$. Luminaire body of die-cast aluminium. Surface coated dark grey. Luminaire body and heat sink form a compact unit. Protection rating: IP20. With an electronic transformer, switchable.

Specification

Model No.	NXAL-082-10
Light Source	10.5W-1050lm-2700K/ 3000K/ 4000K
CRI	90
Driver	O-OnOff/ DIM1-1~10V/ DIM2-DALI
Reflector color	Black/ White
Light beam angle	15°/ 24°/ 38°/ 48°
Accessories	Honeycomb/ Softening Lens
Dimension	Ø82 mm*H85 mm
Cut-out	Ø75 mm



ALITA NXAL-082-12

Vendor: 360LAMP

Light Source: 12.5W-1092lm-2700K , 12.5W-1092lm-3000K , 12.5W-1092lm-4000K ,

Driver: O-On/Off , DIM1-1~10V , DIM2-DALI ,

Accessories: None , Honeycomb , Softening Lens ,

BUY NOW

Description

Compact LED downlight with round white frame. Recessed downlight for cut-out ceiling openings. Tool-free ceiling installation via rapid-mounting springs. Cut-out opening Ø 75 mm, Recess depth 85 mm. Aluminium reflector highly specular anodized. Glare evaluation according to UGR < 19. Configured with one LED spot module. Light colour warm white, correlated colour temperature (CCT) 2700 K, 3000K and 4000K. General colour rendering index (CRI) $R_a > 90$. Mean rated service life $L_{70}(t_q\ 25\ ^\circ\text{C}) = 50,000\ \text{h}$. Luminaire body of die-cast aluminium. Surface coated dark grey. Luminaire body and heat sink form a compact unit. Protection rating: IP20. With an electronic transformer, switchable.

Specification

Model No.	NXAL-082-12
Light Source	12.5W-1092lm-2700K/ 3000K/ 4000K
CRI	90
Driver	O-OnOff/ DIM1-1~10V/ DIM2-DALI
Reflector color	Black/ White
Light beam angle	15°/ 24°/ 38°/ 48°
Accessories	Honeycomb/ Softening Lens
Dimension	Ø82 mm*H85 mm
Cut-out	Ø75 mm



ALITA NXAL-115-30

Vendor: 360LAMP

Light Source: 30W-3300lm-2700K , 30W-3300lm-3000K , 30W-3300lm-4000K ,

Driver: O-On/Off , DIM1-1~10V , DIM2-DALI ,

Accessories: None , Honeycomb , Softening Lens ,

BUY NOW

Description

Compact LED downlight with round white frame. Recessed downlight for cut-out ceiling openings. Tool-free ceiling installation via rapid-mounting springs. Cut-out opening Ø 100 mm, Recess depth 120 mm. Aluminium reflector highly specular anodized. Glare evaluation according to UGR < 19. Configured with one LED spot module. Light colour warm white, correlated colour temperature (CCT) 2700 K, 3000K and 4000K. General colour rendering index (CRI) R_a > 90. Mean rated service life L₇₀(t_q 25 °C) = 50,000 h. Luminaire body of die-cast aluminium. Surface coated dark grey. Luminaire body and heat sink form a compact unit. Protection rating: IP20. With an electronic transformer, switchable.

Specification

Model No.	NXAL-115-30
Light Source	30W-3300lm-2700K/ 3000K/ 4000K
CRI	90
Driver	O-OnOff/ DIM1-1~10V/ DIM2-DALI
Reflector color	Black/ White
Light beam angle	15°/ 24°/ 38°/ 48°
Accessories	Honeycomb/ Softening Lens
Dimension	Ø115 mm*H120 mm
Cut-out	Ø100 mm



ALITA NXAL-115-40

Vendor: 360LAMP

Light Source: 40W-4400lm-2700K , 40W-4400lm-3000K , 40W-4400lm-4000K ,

Driver: O-On/Off , DIM1-1~10V , DIM2-DALI ,

Accessories: None , Honeycomb , Softening Lens ,

[BUY NOW](#)

Description

Compact LED downlight with round white frame. Recessed downlight for cut-out ceiling openings. Tool-free ceiling installation via rapid-mounting springs. Cut-out opening Ø 100 mm, Recess depth 120 mm. Aluminium reflector highly specular anodized. Glare evaluation according to UGR < 19. Configured with one LED spot module. Light colour warm white, correlated colour temperature (CCT) 2700 K, 3000K and 4000K. General colour rendering index (CRI) R_a > 90. Mean rated service life L₇₀(t_q 25 °C) = 50,000 h. Luminaire body of die-cast aluminium. Surface coated dark grey. Luminaire body and heat sink form a compact unit. Protection rating: IP20. With an electronic transformer, switchable.

Specification

Model No.	NXAL-115-40
Light Source	40W-4400lm-2700K/ 3000K/ 4000K
CRI	90
Driver	O-OnOff/ DIM1-1~10V/ DIM2-DALI
Reflector color	Black/ White
Light beam angle	15°/ 24°/ 38°/ 48°
Accessories	Honeycomb/ Softening Lens
Dimension	Ø115 mm*H120 mm
Cut-out	Ø100 mm



ALITA TRIMLESS ADJUSTABLE NXAL-065-05-TL-AD

Vendor: 360LAMP

Light Source: 5.3W-520lm-2700K , 5.3W-520lm-3000K , 5.3W-520lm-4000K ,

Driver: O-On/Off , DIM1-1~10V , DIM2-DALI ,

Accessories: None , Honeycomb , Softening Lens ,

BUY NOW

Description

Adjustable compact LED trimless downlight with round construction. Recessed downlight for cut-out ceiling openings. Tool-free ceiling installation via rapid-mounting frame. Cut-out opening Ø 65 mm, Recess depth 80 mm. Aluminium reflector highly specular anodized. Glare evaluation according to UGR < 19. Configured with one LED adjustable spot module. Light colour warm white, correlated colour temperature (CCT) 2700 K, 3000K and 4000K. General colour rendering index (CRI) $R_a > 90$. Mean rated service life $L_{70}(t_q\ 25\ ^\circ C) = 50,000\ h$. Luminaire body of die-cast aluminium. Surface coated dark grey. Luminaire body and heat sink form a compact unit. Protection rating: IP20. With an electronic transformer, switchable.

Specification

Model No.	NXAL-065-05-TL-AD
Light Source	5.3W-520lm-2700K/ 3000K/ 4000K
CRI	90
Driver	O-OnOff/ DIM1-1~10V/ DIM2-DALI
Reflector color	Black/ White
Light beam angle	15°/ 24°/ 38°/ 48°
Accessories	Honeycomb/ Softening Lens
Dimension	Ø65 mm*H80 mm
Cut-out	Ø65 mm



ALITA TRIMLESS ADJUSTABLE NXAL-065-08-TL-AD

Vendor: 360LAMP

Light Source: 8.3W-788lm-2700K , 8.3W-788lm-3000K , 8.3W-788lm-4000K ,

Driver: O-On/Off , DIM1-1~10V , DIM2-DALI ,

Accessories: None , Honeycomb , Softening Lens ,

BUY NOW

Description

Adjustable compact LED trimless downlight with round construction. Recessed downlight for cut-out ceiling openings. Tool-free ceiling installation via rapid-mounting frame. Cut-out opening Ø 65 mm, Recess depth 80 mm. Aluminium reflector highly specular anodized. Glare evaluation according to UGR < 19. Configured with one LED adjustable spot module. Light colour warm white, correlated colour temperature (CCT) 2700 K, 3000K and 4000K. General colour rendering index (CRI) $R_a > 90$. Mean rated service life $L_{70}(t_q\ 25\ ^\circ\text{C}) = 50,000\ \text{h}$. Luminaire body of die-cast aluminium. Surface coated dark grey. Luminaire body and heat sink form a compact unit. Protection rating: IP20. With an electronic transformer, switchable.

Specification

Model No.	NXAL-065-08-TL-AD
Light Source	8.3W-788lm-2700K/ 3000K/ 4000K
CRI	90
Driver	O-OnOff/ DIM1-1~10V/ DIM2-DALI
Reflector color	Black/ White
Light beam angle	15°/ 24°/ 38°/ 48°
Accessories	Honeycomb/ Softening Lens
Dimension	Ø65 mm*H80 mm
Cut-out	Ø65 mm



ALITA TRIMLESS ADJUSTABLE NXAL-075-08-TL-AD

Vendor: 360LAMP

Light Source: 8.3W-788lm-2700K , 8.3W-788lm-3000K , 8.3W-788lm-4000K ,

Driver: O-On/Off , DIM1-1~10V , DIM2-DALI ,

Accessories: None , Honeycomb , Softening Lens ,

BUY NOW

Description

Adjustable compact LED trimless downlight with round construction. Recessed downlight for cut-out ceiling openings. Tool-free ceiling installation via rapid-mounting springs. Cut-out opening Ø 75 mm, Recess depth 85 mm. Aluminium reflector highly specular anodized. Glare evaluation according to UGR < 19. Configured with one LED adjustable spot module. Light colour warm white, correlated colour temperature (CCT) 2700 K, 3000K and 4000K. General colour rendering index (CRI) $R_a > 90$. Mean rated service life $L_{70}(t_q 25\text{ }^{\circ}\text{C}) = 50,000\text{ h}$. Luminaire body of die-cast aluminium. Surface coated dark grey. Luminaire body and heat sink form a compact unit. Protection rating: IP20. With an electronic transformer, switchable.

Specification

Model No.	NXAL-075-08-TL-AD
Light Source	8.3W-788lm-2700K/ 3000K/ 4000K
CRI	90
Driver	O-OnOff/ DIM1-1~10V/ DIM2-DALI
Reflector color	Black/ White
Light beam angle	15°/ 24°/ 38°/ 48°
Accessories	Honeycomb/ Softening Lens
Dimension	Ø75 mm*H85 mm
Cut-out	Ø75 mm



ALITA TRIMLESS ADJUSTABLE NXAL-075-10-TL-AD

Vendor: 360LAMP

Light Source: 10.5W-1050lm-2700K , 10.5W-1050lm-3000K , 10.5W-1050lm-4000K ,

Driver: O-On/Off , DIM1-1~10V , DIM2-DALI ,

Accessories: None , Honeycomb , Softening Lens ,

BUY NOW

Description

Adjustable compact LED trimless downlight with round construction. Recessed downlight for cut-out ceiling openings. Tool-free ceiling installation via rapid-mounting springs. Cut-out opening Ø 75 mm, Recess depth 85 mm. Aluminium reflector highly specular anodized. Glare evaluation according to UGR < 19. Configured with one LED adjustable spot module. Light colour warm white, correlated colour temperature (CCT) 2700 K, 3000K and 4000K. General colour rendering index (CRI) $R_a > 90$. Mean rated service life $L_{70}(t_q\ 25\ ^\circ C) = 50,000\ h$. Luminaire body of die-cast aluminium. Surface coated dark grey. Luminaire body and heat sink form a compact unit. Protection rating: IP20. With an electronic transformer, switchable.

Specification

Model No.	NXAL-075-10-TL-AD
Light Source	10.5W-1050lm-2700K/ 3000K/ 4000K
CRI	90
Driver	O-OnOff/ DIM1-1~10V/ DIM2-DALI
Reflector color	Black/ White
Light beam angle	15°/ 24°/ 38°/ 48°
Accessories	Honeycomb/ Softening Lens
Dimension	Ø75 mm*H85 mm
Cut-out	Ø75 mm



ALITA TRIMLESS ADJUSTABLE NXAL-075-12-TL-AD

Vendor: 360LAMP

Light Source: 12.5W-1092lm-2700K , 12.5W-1092lm-3000K , 12.5W-1092lm-4000K ,

Driver: O-On/Off , DIM1-1~10V , DIM2-DALI ,

Accessories: None , Honeycomb , Softening Lens ,

BUY NOW

Description

Adjustable compact LED trimless downlight with round construction. Recessed downlight for cut-out ceiling openings. Tool-free ceiling installation via rapid-mounting springs. Cut-out opening Ø 75 mm, Recess depth 85 mm. Aluminium reflector highly specular anodized. Glare evaluation according to UGR < 19. Configured with one LED adjustable spot module. Light colour warm white, correlated colour temperature (CCT) 2700 K, 3000K and 4000K. General colour rendering index (CRI) $R_a > 90$. Mean rated service life $L_{70}(t_q\ 25\ ^\circ\text{C}) = 50,000\ \text{h}$. Luminaire body of die-cast aluminium. Surface coated dark grey. Luminaire body and heat sink form a compact unit. Protection rating: IP20. With an electronic transformer, switchable.

Specification

Model No.	NXAL-075-12-TL-AD
Light Source	12.5W-1092lm-2700K/ 3000K/ 4000K
CRI	90
Driver	O-OnOff/ DIM1-1~10V/ DIM2-DALI
Reflector color	Black/ White
Light beam angle	15°/ 24°/ 38°/ 48°
Accessories	Honeycomb/ Softening Lens
Dimension	Ø75 mm*H85 mm
Cut-out	Ø75 mm



ALITA TRIMLESS NXAL-065-05-TL

Vendor: 360LAMP

Light Source: 5.3W-520lm-2700K , 5.3W-520lm-3000K , 5.3W-520lm-4000K ,

Driver: O-On/Off , DIM1-1~10V , DIM2-DALI ,

Accessories: None , Honeycomb , Softening Lens ,

BUY NOW

Description

Compact LED trimless downlight with round construction. Recessed downlight for cut-out ceiling openings. Tool-free ceiling installation via rapid-mounting frame. Cut-out opening Ø 65 mm, Recess depth 80 mm. Aluminium reflector highly specular anodized. Glare evaluation according to UGR < 19. Configured with one LED spot module. Light colour warm white, correlated colour temperature (CCT) 2700 K, 3000K and 4000K. General colour rendering index (CRI) R_a > 90. Mean rated service life L₇₀(t_q 25 °C) = 50,000 h. Luminaire body of die-cast aluminium. Surface coated dark grey. Luminaire body and heat sink form a compact unit. Protection rating: IP20. With an electronic transformer, switchable.

Specification

Model No.	NXAL-065-05-TL
Light Source	5.3W-520lm-2700K/ 3000K/ 4000K
CRI	90
Driver	O-OnOff/ DIM1-1~10V/ DIM2-DALI
Reflector color	Black/ White
Light beam angle	15°/ 24°/ 38°/ 48°
Accessories	Honeycomb/ Softening Lens
Dimension	Ø65 mm*H80 mm
Cut-out	Ø65 mm



ALITA TRIMLESS NXAL-065-08-TL

Vendor: 360LAMP

Light Source: 8.3W-788lm-2700K , 8.3W-788lm-3000K , 8.3W-788lm-4000K ,

Driver: O-On/Off , DIM1-1~10V , DIM2-DALI ,

Accessories: None , Honeycomb , Softening Lens ,

BUY NOW

Description

Compact LED trimless downlight with round construction. Recessed downlight for cut-out ceiling openings. Tool-free ceiling installation via rapid-mounting frame. Cut-out opening Ø 65 mm, Recess depth 80 mm. Aluminium reflector highly specular anodized. Glare evaluation according to UGR < 19. Configured with one LED spot module. Light colour warm white, correlated colour temperature (CCT) 2700 K, 3000K and 4000K. General colour rendering index (CRI) $R_a > 90$. Mean rated service life $L_{70}(t_q\ 25\ ^\circ\text{C}) = 50,000\ \text{h}$. Luminaire body of die-cast aluminium. Surface coated dark grey. Luminaire body and heat sink form a compact unit. Protection rating: IP20. With an electronic transformer, switchable.

Specification

Model No.	NXAL-065-08-TL
Light Source	8.3W-788lm-2700K/ 3000K/ 4000K
CRI	90
Driver	O-OnOff/ DIM1-1~10V/ DIM2-DALI
Reflector color	Black/ White
Light beam angle	15°/ 24°/ 38°/ 48°
Accessories	Honeycomb/ Softening Lens
Dimension	Ø65 mm*H80 mm
Cut-out	Ø65 mm



ALITA TRIMLESS NXAL-075-08-TL

Vendor: 360LAMP

Light Source: 8.3W-788lm-2700K , 8.3W-788lm-3000K , 8.3W-788lm-4000K ,

Driver: O-On/Off , DIM1-1~10V , DIM2-DALI ,

Accessories: None , Honeycomb , Softening Lens ,

BUY NOW

Description

Compact LED trimless downlight with round construction. Recessed downlight for cut-out ceiling openings. Tool-free ceiling installation via rapid-mounting springs. Cut-out opening Ø 75 mm, Recess depth 85 mm. Aluminium reflector highly specular anodized. Glare evaluation according to UGR < 19. Configured with one LED spot module. Light colour warm white, correlated colour temperature (CCT) 2700 K, 3000K and 4000K. General colour rendering index (CRI) $R_a > 90$. Mean rated service life $L_{70}(t_q\ 25\ ^\circ\text{C}) = 50,000\ \text{h}$. Luminaire body of die-cast aluminium. Surface coated dark grey. Luminaire body and heat sink form a compact unit. Protection rating: IP20. With an electronic transformer, switchable.

Specification

Model No.	NXAL-075-08-TL
Light Source	8.3W-788lm-2700K/ 3000K/ 4000K
CRI	90
Driver	O-OnOff/ DIM1-1~10V/ DIM2-DALI
Reflector color	Black/ White
Light beam angle	15°/ 24°/ 38°/ 48°
Accessories	Honeycomb/ Softening Lens
Dimension	Ø75 mm*H85 mm
Cut-out	Ø75 mm



ALITA TRIMLESS NXAL-075-10-TL

Vendor: 360LAMP

Light Source: 10.5W-1050lm-2700K , 10.5W-1050lm-3000K , 10.5W-1050lm-4000K ,

Driver: O-On/Off , DIM1-1~10V , DIM2-DALI ,

Accessories: None , Honeycomb , Softening Lens ,

BUY NOW

Description

Compact LED trimless downlight with round construction. Recessed downlight for cut-out ceiling openings. Tool-free ceiling installation via rapid-mounting springs. Cut-out opening Ø 75 mm, Recess depth 85 mm. Aluminium reflector highly specular anodized. Glare evaluation according to UGR < 19. Configured with one LED spot module. Light colour warm white, correlated colour temperature (CCT) 2700 K, 3000K and 4000K. General colour rendering index (CRI) $R_a > 90$. Mean rated service life $L_{70}(t_q\ 25\ ^\circ\text{C}) = 50,000\ \text{h}$. Luminaire body of die-cast aluminium. Surface coated dark grey. Luminaire body and heat sink form a compact unit. Protection rating: IP20. With an electronic transformer, switchable.

Specification

Model No.	NXAL-075-10-TL
Light Source	10.5W-1050lm-2700K/ 3000K/ 4000K
CRI	90
Driver	O-OnOff/ DIM1-1~10V/ DIM2-DALI
Reflector color	Black/ White
Light beam angle	15°/ 24°/ 38°/ 48°
Accessories	Honeycomb/ Softening Lens
Dimension	Ø75 mm*H85 mm
Cut-out	Ø75 mm



ALITA TRIMLESS NXAL-075-12-TL

Vendor: 360LAMP

Light Source: 12.5W-1092lm-2700K , 12.5W-1092lm-3000K , 12.5W-1092lm-4000K ,

Driver: O-On/Off , DIM1-1~10V , DIM2-DALI ,

Accessories: None , Honeycomb , Softening Lens ,

BUY NOW

Description

Compact LED trimless downlight with round construction. Recessed downlight for cut-out ceiling openings. Tool-free ceiling installation via rapid-mounting springs. Cut-out opening Ø 75 mm, Recess depth 85 mm. Aluminium reflector highly specular anodized. Glare evaluation according to UGR < 19. Configured with one LED spot module. Light colour warm white, correlated colour temperature (CCT) 2700 K, 3000K and 4000K. General colour rendering index (CRI) $R_a > 90$. Mean rated service life $L_{70}(t_q\ 25\ ^\circ\text{C}) = 50,000\ \text{h}$. Luminaire body of die-cast aluminium. Surface coated dark grey. Luminaire body and heat sink form a compact unit. Protection rating: IP20. With an electronic transformer, switchable.

Specification

Model No.	NXAL-075-12-TL
Light Source	12.5W-1092lm-2700K/ 3000K/ 4000K
CRI	90
Driver	O-OnOff/ DIM1-1~10V/ DIM2-DALI
Reflector color	Black/ White
Light beam angle	15°/ 24°/ 38°/ 48°
Accessories	Honeycomb/ Softening Lens
Dimension	Ø75 mm*H85 mm
Cut-out	Ø75 mm

Phone: 400 608 0665

Beijing: (+86 10) 64913737

Shanghai: (+86 21) 65310097

Email: billniu@360lamps.com

Website: <https://shop.360lamps.com>